

## DISTRIBUTION BOXES

*Distribution boxes for flexible current supply, portable and handy, with high resistance to weather and chemicals. All combinations are tested for electrical safety and quality. The products are widely used in the following sites.*

- > Repair, extension and demolition work on existing buildings.
- > Construction sites
- > Exhibition center
- > Factories

### *Characteristics*

- > IP44 protection degree against dust and liquid bodies
- > IK8 mechanical protection degree
- > High quality thermoplastic material
- > Available component preset as requested



A06MA01-4



Dimension	425.5 × 136 × 94.5
Input:	1 CEE L plug 16A-IP44 2P+E 230V~ 3G2.5sq mm cable 2.2m
Output	3 CEE L Socket 16A-IP44 2P+E 230V~
Protection fuse	1 RCD 25A 2P 0.03A 230V~ 3 MCB 16A 1P 230V~
Protection degree	IP44 Splashproof

A06MB01-4



Dimension	425.5 × 136 × 94.5
Input:	1 CEE L plug 16A-IP44 2P+E 230V~ 3G2.5sq mm cable 2.2m
Output	6 Socket (DIN 49440)16A-IP44 2P+E 230V~
Protection fuse	1 RCD 25A 2P 0.03A 230V~ 3 MCB 16A 1P 230V~
Protection degree	IP44 Splashproof

A06MC01-4



Dimension	425.5 × 136 × 94.5
Input:	1 CEE L plug 16A-IP44 2P+E 230V~ 3G2.5sq mm cable 2.2m
Output	6 Socket (BS1363) 13A 2P+E 230V~
Protection fuse	1 RCD 25A 2P 0.03A 230V~ 3 MCB 13A 1P 230V~
Protection degree	IP44 Splashproof

A06MD01-4



Dimension	425.5 × 136 × 94.5
Input:	1 CEE L plug 16A-IP44 2P+E 230V~ 3G2.5sq mm cable 2.2m
Output	2 Socket(DIN 49440) 16A-IP44 2P+E 230V~ 2 CEE L Socket 16A-IP44 2P+E 230V~
Protection fuse	1 RCD 25A 2P 0.03A 230V~ 3 MCB 16A 1P 230V~
Protection degree	IP44 Splashproof

A06ME01-4



Dimension	425.5 × 136 × 94.5
Input:	1 CEE L plug 16A-IP44 2P+E 230V~ 3G2.5sq mm cable 2.2m
Output	2 Socket(BS1363) 13A-IP44 2P+E 230V~ 2 CEE L Socket 16A-IP44 2P+E 230V~
Protection fuse	1 RCD 25A 2P 0.03A 230V~ 3 MCB 16A 1P 230V~
Protection degree	IP44 Splashproof

A06MF01-4



Dimension	425.5 × 136 × 94.5
Input:	1 CEE L plug 32A-IP44 3P+N+E 415V~ 5G4.0sq mm cable 2.2m
Output	2 Socket(DIN 49440) 16A-IP44 2P+E 230V~ 1 CEE L Socket 16A-IP44 2P+E 230V~ 1 CEE L Socket 32A-IP44 3P+N+E 415V~
Protection fuse	1 RCD 40A 4P 0.03A 400V~ 2 MCB 16A 1P 230V~
Protection degree	IP44 Splashproof

A06MG01-4



Dimension	425.5 × 136 × 94.5
Input	1 CEE L plug 32A-IP44 3P+N+E 415V~ 5G4.0sq mm cable 2.2m
Output	2 Socket (BS1363) 13A-IP44 2P+E 230V~ 1 CEE L Socket 16A-IP44 2P+E 230V~ 1 CEE L Socket 32A-IP44 3P+N+E 415V~
Protection fuse	1 RCD 40A 4P 0.03A 400V~ 2 MCB 16A 1P 230V~
Protection degree	IP44 Splashproof

A10MA01-4



Dimension	410 × 210 × 97.5
Input:	1 CEE L plug 16A-IP44 2P+E 230V~ 3G2.5sq mm cable 2.2m
Output	2 CEE INTERLOCK Socket 16A-IP44 2P+E 230V~
Protection fuse	1 RCD 25A 2P 0.03A 230V~ 2 MCB 16A 1P 230V~
Protection degree	IP44 Splashproof

A10MA02-4



Dimension	410 × 210 × 97.5
Input:	1 CEE L plug 16A-IP44 3P+E 380V~ 4G2.5sq mm cable 2.2m
Output	2 CEE INTERLOCK Socket 16A-IP44 3P+E 380V~
Protection fuse	1 RCD 25A 4P 0.03A 400V~ 2 MCB 16A 3P 400V~
Protection degree	IP44 Splashproof

### A10MA03-4



Dimension	410 × 210 × 97.5
Input	1 CEE L plug 16A-IP44 3P+N+E 415V~ 5G2.5sq mm cable 2.2m
Output	2 CEE INTERLOCK Socket 16A-IP44 3P+N+E 415V~
Protection fuse	1 RCD 25A 4P 0.03A 400V~ 2 MCB 16A 3P 400V~
Protection degree	IP44 Splashproof

### A10MA04-4



Dimension	410 × 210 × 97.5
Input	1 CEE L plug 32A-IP44 2P+E 230V~ 3G4.0sq mm cable 2.2m
Output	2 CEE INTERLOCK Socket 32A-IP44 2P+E 230V~
Protection fuse	1 RCD 40A 2P 0.03A 230V~ 2 MCB 32A 1P 230V~
Protection degree	IP44 Splashproof

### A10MA05-4



Dimension	410 × 210 × 97.5
Input	1 CEE L plug 32A-IP44 3P+E 380V~ 4G4.0sq mm cable 2.2m
Output	2 CEE INTERLOCK Socket 32A-IP44 3P+E 380V~
Protection fuse	1 RCD 40A 4P 0.03A 400V~ 2 MCB 32A 3P 400V~
Protection degree	IP44 Splashproof



### A10MA06-4



Dimension	410 × 210 × 97.5
Input	1 CEE L plug 32A-IP44 3P+N+E 415V~ 5G4.0sq mm cable 2.2m
Output	2 CEE INTERLOCK Socket 32A-IP44 3P+N+E 415V~
Protection fuse	1 RCD 40A 4P 0.03A 400V~ 2 MCB 32A 3P 400V~
Protection degree	IP44 Splashproof

### A10MA07-4



Dimension	410 × 210 × 97.5
Input	1 CEE L plug 16A-IP44 3P+N+E 415V~ 5G2.5sq mm cable 2.2m
Output	1 CEE INTERLOCK Socket 16A-IP44 2P+E 230V~ 1 CEE INTERLOCK Socket 16A-IP44 3P+N+E 415V~
Protection fuse	1 RCD 25A 4P 0.03A 400V~ 1 MCB 16A 1P 230V~ 1 MCB 16A 3P 400V~
Protection degree	IP44 Splashproof

### A10MA08-4



Dimension	410 × 210 × 97.5
Input	1 CEE L plug 32A-IP44 3P+N+E 415V~ 5G4.0sq mm cable 2.2m
Output	1 CEE INTERLOCK Socket 32A-IP44 2P+E 230V~ 1 CEE INTERLOCK Socket 32A-IP44 3P+N+E 415V~
Protection fuse	1 RCD 40A 4P 0.03A 400V~ 1 MCB 32A 1P 230V~ 1 MCB 32A 3P 400V~
Protection degree	IP44 Splashproof

A10MA09-4



Dimension	410 × 210 × 97.5
Input	1 CEE L plug 32A-IP44 3P+N+E 415V~ 5G4.0sq mm cable 2.2m
Output	1 CEE INTERLOCK Socket 16A-IP44 3P+N+E 415V~ 1 CEE INTERLOCK Socket 32A-IP44 3P+N+E 415V~
Protection fuse	1 RCD 40A 4P 0.03A 400V~ 1 MCB 16A 3P 400V~ 1 MCB 32A 3P 400V~
Protection degree	IP44 Splashproof

A10MB01-4



Dimension	410 × 210 × 97.5
Input	1 CEE L plug 16A-IP44 2P+E 230V~ 3G2.5sq mm cable 2.2m
Output	4 CEE L Socket 16A-IP44 2P+E 230V~
Protection fuse	1 RCD 25A 2P 0.03A 230V~ 4 MCB 16A 1P 230V~
Protection degree	IP44 Splashproof

A10MB02-4



Dimension	410 × 210 × 97.5
Input	1 CEE L plug 16A-IP44 3P+N+E 415V~ 5G2.5sq mm cable 2.2m
Output	2 CEE L Socket 16A-IP44 2P+E 230V~ 2 CEE L Socket 16A-IP44 3P+N+E 415V~
Protection fuse	1 RCD 25A 4P 0.03A 400V~ 2 MCB 16A 1P 230V~ 1 MCB 16A 3P 400V~
Protection degree	IP44 Splashproof

A10MB03-4



Dimension	410 × 210 × 97.5
Input	1 CEE L plug 32A-IP44 2P+E 230V~ 3G4.0sq mm cable 2.2m
Output	4 CEE L Socket 32A-IP44 2P+E 230V~
Protection fuse	1 RCD 40A 2P 0.03A 230V~ 4 MCB 32A 1P 230V~
Protection degree	IP44 Splashproof

A10MB04-4



Dimension	410 × 210 × 97.5
Input	1 CEE L plug 16A-IP67 2P+E 230V~ 3G2.5sq mm cable 2.2m
Output	4 CEE L Socket 16A-IP67 2P+E 230V~
Protection fuse	1 RCD 25A 2P 0.03A 230V~ 4 MCB 16A 1P 230V~
Protection degree	IP55 Waterproof

A10MB05-4



Dimension	410 × 210 × 97.5
Input	1 CEE L plug 16A-IP67 3P+N+E 415V~ 5G2.5sq mm cable 2.2m
Output	2 CEE L Socket 16A-IP67 2P+E 230V~ 2 CEE L Socket 16A-IP67 3P+N+E 415V~
Protection fuse	1 RCD 25A 4P 0.03A 400V~ 2 MCB 16A 1P 230V~ 1 MCB 16A 3P 400V~
Protection degree	IP55 Waterproof



A10MB06-4



Dimension	410 × 210 × 97.5
Input	1 CEE L plug 32A-IP67 2P+E 230V~ 3G4.0sq mm cable 2.2m
Output	4 CEE L Socket 32A-IP67 2P+E 230V~
Protection fuse	1 RCD 40A 2P 0.03A 230V~ 4 MCB 32A 1P 230V~
Protection degree	IP55 Waterproof

A10MC01-4



Dimension	410 × 210 × 97.5
Input	1 CEE L plug 32A-IP44 3P+N+E 415V~ 5G4.0sq mm cable 2.2m
Output	2 CEE L Socket 32A-IP44 2P+E 230V~ 2 CEE L Socket 32A-IP44 3P+N+E 415V~
Protection fuse	1 RCD 40A 4P 0.03A 400V~ 2 MCB 32A 1P 230V~ 1 MCB 32A 3P 400V~
Protection degree	IP44 Splashproof

A10MC02-4



Dimension	410 × 210 × 97.5
Input	1 CEE L plug 32A-IP44 3P+N+E 415V~ 5G4.0sq mm cable 2.2m
Output	2 CEE L Socket 16A-IP44 3P+N+E 415V~ 2 CEE L Socket 32A-IP44 3P+N+E 415V~
Protection fuse	1 RCD 40A 4P 0.03A 400V~ 1 MCB 16A 3P 400V~ 1 MCB 32A 3P 400V~
Protection degree	IP44 Splashproof

A10MC03-4



Dimension	410 × 210 × 97.5
Input	1 CEE HTN plug 32A-IP67 3P+N+E 415V~ 5G4.0sq mm cable 2.2m
Output	2 CEE HTN Socket 32A-IP67 2P+E 230V~ 2 CEE HTN Socket 32A-IP67 3P+N+E 415V~
Protection fuse	1 RCD 40A 4P 0.03A 400V~ 2 MCB 32A 1P 230V~ 1 MCB 32A 3P 400V~
Protection degree	IP55 Waterproof

A10MC04-4



Dimension	410 × 210 × 97.5
Input	1 CEE HTN plug 32A-IP67 3P+N+E 415V~ 5G4.0sq mm cable 2.2m
Output	2 CEE HTN Socket 16A-IP67 3P+N+E 415V~ 2 CEE HTN Socket 32A-IP67 3P+N+E 415V~
Protection fuse	1 RCD 40A 4P 0.03A 400V~ 1 MCB 16A 3P 400V~ 1 MCB 32A 3P 400V~
Protection degree	IP55 Waterproof

B11MA02-2



Dimension	319 × 273 × 101
Input	1 CEE HTN plug 16A-IP44 3P+N+E 415V~
Output	4 Socket (DIN 49440) 16A-IP44 230V~ 1 CEE HTN Socket 16A-IP44 3P+N+E 415V~ 1 CEE HTN Socket 16A-IP44 3P+E 380V~
Protection fuse	1 RCD 25A 4P 0.03A 400V~ 1 MCB 16A 3P 400V~ 4 MCB 16A 1P 230V~
Protection degree	IP44 Splashproof

### B11MA03-4



Dimension	319 × 273 × 101
Input	1 CEE L plug 16A-IP44 3P+N+E 415V~ 5G2.5sq mm cable 2.2m
Output	4 Socket (DIN 49440) 16A-IP44 230V~ 1 CEE L Socket 16A-IP44 3P+N+E 415V~ 1 CEE L Socket 16A-IP44 3P+E 380V~ 1 CEE L Socket 16A-IP44 2P+E 230V~
Protection fuse	2 MCB 16A 3P 400V~ 5 MCB 16A 1P 230V~
Protection degree	IP44 Splashproof

### B11MA09-2



Dimension	319 × 273 × 101
Input	1 CEE L plug 16A-IP44 3P+N+E 415V~
Output	4 Socket (DIN 49440) 16A-IP44 230V~ 2 CEE L Socket 16A-IP44 3P+N+E 415V~
Protection fuse	1 RCD 25A 4P 0.03A 400V~ 1 MCB 16A 3P 400V~ 4 MCB 16A 1P 230V~
Protection degree	IP44 Splashproof

### B11MA10-2



Dimension	319 × 273 × 101
Input	1 CEE L plug 32A-IP44 3P+N+E 415V~
Output	4 Socket (DIN 49440) 16A-IP44 230V~ 1 CEE L Socket 32A-IP44 3P+N+E 415V~ 1 CEE L Socket 16A-IP44 3P+N+E 415V~
Protection fuse	1 RCD 40A 4P 0.03A 400V~ 1 MCB 16A 3P 400V~ 4 MCB 16A 1P 230V~
Protection degree	IP44 Splashproof

### B11MB02-2



Dimension	319 × 273 × 101
Input	1 CEE L plug 16A-IP44 3P+N+E 415V~
Output	3 CEE L Socket 16A-IP44 2P+E 230V~ 1 CEE L Socket 16A-IP44 3P+N+E 415V~ 1 CEE L Socket 16A-IP44 3P+E 380V~
Protection fuse	1 RCD 25A 4P 0.03A 400V~ 1 MCB 16A 3P 400V~ 3 MCB 16A 1P 230V~
Protection degree	IP44 Splashproof

### B11MB01-4



Dimension	319 × 273 × 101
Input	1 CEE L plug 32A-IP44 3P+N+E 415V~ 5G4.0sq mm cable 2.2m
Output	1 CEE L Socket 32A-IP44 3P+N+E 415V~ 1 CEE L Socket 16A-IP44 3P+N+E 415V~ 3 CEE L Socket 16A-IP44 2P+E 230V~ 1 CEE L Socket 32A-IP44 2P+E 230V~
Protection fuse	1 RCD 40A 4P 0.03A 400V~ 1 MCB 16A 3P 400V~ 1 MCB 32A 1P 230V~ 3 MCB 16A 1P 230V~
Protection degree	IP44 Splashproof

### B11MB03-4



Dimension	319 × 273 × 101
Input	1 CEE L plug 16A-IP44 3P+N+E 415V~ 5G2.5sq mm cable 2.2m
Output	3 CEE L Socket 16A-IP44 2P+E 230V~ 1 CEE L Socket 16A-IP44 3P+N+E 415V~ 1 CEE L Socket 16A-IP44 3P+E 380V~ 1 CEE L Socket 16A-IP44 2P+E 230V~
Protection fuse	2 MCB 16A 3P 400V~ 4 MCB 16A 1P 230V~
Protection degree	IP44 Splashproof

### B11MB09-2



Dimension	319 × 273 × 101
Input	1 CEE L plug 16A-IP44 3P+N+E 415V~
Output	2 CEE L Socket 16A-IP44 3P+N+E 415V~ 3 CEE L Socket 16A-IP44 2P+E 230V~
Protection fuse	1 RCD 25A 4P 0.03A 400V~ 1 MCB 16A 3P 400V~ 3 MCB 16A 1P 230V~
Protection degree	IP44 Splashproof

### B14MA01-2



Dimension	410 × 300 × 96
Input	1 CEE L plug 32A-IP44 3P+N+E 415V~
Output	1 CEE L Socket 32A-IP44 3P+N+E 415V~ 1 CEE L Socket 16A-IP44 3P+N+E 415V~ 4 SCHUKO Socket 16A-IP44 2P+E 230V~
Protection fuse	1 RCD 40A 4P 0.03A 400V~ 1 MCB 32A 3P 400V~ 1 MCB 16A 3P 400V~ 4 MCB 16A 1P 230V~
Protection degree	IP44 Splashproof

### B14MA04-4



Dimension	410 × 300 × 96
Input	1 CEE L plug 32A-IP44 3P+N+E 415V~ 5G4.0sq mm cable 2.2m
Output	1 CEE L Socket 32A-IP44 3P+N+E 415V~ 1 CEE L Socket 16A-IP44 3P+N+E 415V~ 1 CEE L Socket 16A-IP44 3P+E 380V~ 4 SCHUKO Socket 16A-IP44 2P+E 230V~
Protection fuse	1 RCD 40A 4P 0.03A 400V~ 2 MCB 16A 3P 400V~ 4 MCB 16A 1P 230V~
Protection degree	IP44 Splashproof

### B14MA02-4



Dimension	410 × 300 × 96
Input	1 CEE L plug 32A-IP44 3P+N+E 415V~ 5G4.0sq mm cable 2.2m
Output	1 CEE L Socket 32A-IP44 3P+N+E 415V~ 2 CEE L Socket 16A-IP44 3P+N+E 415V~ 4 SCHUKO Socket 16A-IP44 2P+E 230V~
Protection fuse	1 RCD 40A 4P 0.03A 400V~ 2 MCB 16A 3P 400V~ 4 MCB 16A 1P 230V~
Protection degree	IP44 Splashproof

### B14MB03-2



Dimension	410 × 300 × 96
Input	1 CEE L plug 32A-IP44 3P+N+E 415V~
Output	2 CEE L Socket 16A-IP44 3P+N+E 415V~ 4 SCHUKO Socket 16A-IP44 2P+E 230V~
Protection fuse	1 RCD 40A 4P 0.03A 400V~ 2 MCB 16A 3P 400V~ 4 MCB 16A 1P 230V~
Protection degree	IP44 Splashproof

### B14MB01-2



Dimension	410 × 300 × 96
Input	1 CEE L plug 32A-IP44 3P+N+E 415V~
Output	1 CEE L Socket 32A-IP44 3P+N+E 415V~ 1 CEE L Socket 16A-IP44 3P+N+E 415V~ 8 SCHUKO Socket 16A-IP44 2P+E 230V~
Protection fuse	1 RCD 40A 4P 0.03A 400V~ 1 MCB 32A 3P 400V~ 1 MCB 16A 3P 400V~ 4 MCB 16A 1P 230V~
Protection degree	IP44 Splashproof



### B14MB03-2



Dimension	410 × 300 × 96
Input	1 CEE L plug 32A-IP44 3P+N+E 415V~
Output	2 CEE L Socket 16A-IP44 3P+N+E 415V~ 8 SCHUKO Socket 16A-IP44 2P+E 230V~
Protection fuse	1 RCD 40A 4P 0.03A 400V~ 2 MCB 16A 3P 400V~ 4 MCB 16A 1P 230V~
Protection degree	IP44 Splashproof

### B14MC01-2



Dimension	410 × 300 × 96
Input	1 CEE L plug 32A-IP44 3P+N+E 415V~
Output	1 CEE L Socket 16A-IP44 3P+N+E 415V~ 1 CEE L Socket 32A-IP44 3P+N+E 415V~ 3 CEE L Socket 16A-IP44 2P+E 230V~ 4 SCHUKO Socket 16A-IP44 2P+E 230V~
Protection fuse	1 RCD 40A 4P 0.03A 400V~ 1 MCB 16A 3P 400V~ 7 MCB 16A 1P 230V~
Protection degree	IP44 Splashproof

### B14MC05-2



Dimension	410 × 300 × 96
Input	1 CEE L plug 32A-IP44 3P+N+E 415V~
Output	1 CEE L Socket 32A-IP44 3P+N+E 415V~ 1 CEE L Socket 16A-IP44 3P+N+E 415V~ 1 CEE L Socket 16A-IP44 3P+E 380V~ 2 CEE L Socket 16A-IP44 2P+E 230V~ 4 SCHUKO Socket 16A-IP44 2P+E 230V~
Protection fuse	1 RCD 40A 4P 0.03A 400V~ 1 MCB 16A 3P 400V~ 6 MCB 16A 1P 230V~
Protection degree	IP44 Splashproof

B14MC03-2



Dimension	410 × 300 × 96
Input	1 CEE L plug 32A-IP44 3P+N+E 415V~
Output	2 CEE L Socket 16A-IP44 3P+N+E 415V~ 3 CEE L Socket 16A-IP44 2P+E 230V~ 4 SCHUKO Socket 16A-IP44 2P+E 230V~
Protection fuse	1 RCD 40A 4P 0.03A 400V~ 1 MCB 16A 3P 400V~ 7 MCB 16A 1P 230V~
Protection degree	IP44 Splashproof

B06MA01-4



Dimension	340 × 136 × 94.5
Input:	1 CEE L plug 16A-IP44 2P+E 230V~ 3G2.5sq mm cable 2.2m
Output	1 CEE INTERLOCK Socket 16A-IP44 2P+E 230V~
Protection fuse	1 RCD 25A 2P 0.03A 230V~ 1 MCB 16A 2P 230V~
Protection degree	IP44 Splashproof

B06MA02-4



Dimension	340 × 136 × 94.5
Input:	1 CEE L plug 16A-IP44 3P+E 380V~ 4G2.5sq mm cable 2.2m
Output	1 CEE INTERLOCK Socket 16A-IP44 3P+E 380V~
Protection fuse	1 RCD 25A 4P 0.03A 400V~
Protection degree	IP44 Splashproof

B06MA03-4



Dimension	340 × 136 × 94.5
Input	1 CEE L plug 16A-IP44 3P+N+E 415V~ 5G2.5sq mm cable 2.2m
Output	1 CEE INTERLOCK Socket 16A-IP44 3P+N+E 415V~
Protection fuse	1 RCD 25A 4P 0.03A 400V~
Protection degree	IP44 Splashproof

B06MA04-4



Dimension	340 × 136 × 94.5
Input	1 CEE L plug 32A-IP44 2P+E 230V~ 3G4.0sq mm cable 2.2m
Output	1 CEE INTERLOCK Socket 32A-IP44 2P+E 230V~
Protection fuse	1 RCD 32A 2P 0.03A 230V~ 1 MCB 32A 2P 230V~
Protection degree	IP44 Splashproof

B06MA05-4



Dimension	340 × 136 × 94.5
Input	1 CEE L plug 32A-IP44 3P+E 380V~ 4G4.0sq mm cable 2.2m
Output	1 CEE INTERLOCK Socket 32A-IP44 3P+E 380V~
Protection fuse	1 RCD 32A 4P 0.03A 400V~
Protection degree	IP44 Splashproof

B06MA06-4



Dimension	340 × 136 × 94.5
Input	1 CEE L plug 32A-IP44 3P+N+E 415V~ 5G4.0sq mm cable 2.2m
Output	1 CEE INTERLOCK Socket 32A-IP44 3P+N+E 415V~
Protection fuse	1 RCD 32A 4P 0.03A 400V~
Protection degree	IP44 Splashproof

B06MB01-4



Dimension	340 × 136 × 94.5
Input	1 CEE L plug 16A-IP44 2P+E 230V~ 3G2.5sq mm cable 2.2m
Output	2 CEE L Socket 16A-IP44 2P+E 230V~
Protection fuse	1 RCD 25A 2P 0.03A 230V~ 2 MCB 16A 1P 230V~
Protection degree	IP44 Splashproof

B06MB02-4



Dimension	340 × 136 × 94.5
Input	1 CEE L plug 16A-IP44 3P+N+E 415V~ 5G2.5sq mm cable 2.2m
Output	1 CEE L Socket 16A-IP44 2P+E 230V~ 1 CEE L Socket 16A-IP44 3P+N+E 415V~
Protection fuse	1 RCD 25A 4P 0.03A 400V~ 1 MCB 16A 1P 230V~
Protection degree	IP44 Splashproof

B06MB03-4



Dimension	340 × 136 × 94.5
Input	1 CEE L plug 32A-IP44 2P+E 230V~ 3G4.0sq mm cable 2.2m
Output	2 CEE L Socket 32A-IP44 2P+E 230V~
Protection fuse	1 RCD 40A 2P 0.03A 230V~ 2 MCB 32A 1P 230V~
Protection degree	IP44 Splashproof

B06MB04-4



Dimension	340 × 136 × 94.5
Input	1 CEE L plug 16A-IP67 2P+E 230V~ 3G2.5sq mm cable 2.2m
Output	2 CEE L Socket 16A-IP67 2P+E 230V~
Protection fuse	1 RCD 25A 2P 0.03A 230V~ 2 MCB 16A 1P 230V~
Protection degree	IP55 Waterproof

B06MB05-4



Dimension	340 × 136 × 94.5
Input	1 CEE L plug 16A-IP67 3P+N+E 415V~ 5G2.5sq mm cable 2.2m
Output	1 CEE L Socket 16A-IP67 2P+E 230V~ 1 CEE L Socket 16A-IP67 3P+N+E 415V~
Protection fuse	1 RCD 25A 4P 0.03A 400V~ 1 MCB 16A 1P 230V~
Protection degree	IP55 Waterproof

B06MB06-4



Dimension	340 × 136 × 94.5
Input	1 CEE L plug 32A-IP67 2P+E 230V~ 3G4.0sq mm cable 2.2m
Output	2 CEE L Socket 32A-IP67 2P+E 230V~
Protection fuse	1 RCD 40A 2P 0.03A 230V~ 2 MCB 32A 1P 230V~
Protection degree	IP55 Waterproof

B06MC01-4



Dimension	340 × 136 × 94.5
Input	1 CEE L plug 32A-IP44 3P+N+E 415V~ 5G4.0sq mm cable 2.2m
Output	1 CEE L Socket 32A-IP44 2P+E 230V~ 1 CEE L Socket 32A-IP44 3P+N+E 415V~
Protection fuse	1 RCD 40A 4P 0.03A 400V~ 1 MCB 32A 1P 230V~
Protection degree	IP44 Splashproof

B06MC02-4



Dimension	340 × 136 × 94.5
Input	1 CEE L plug 32A-IP67 3P+N+E 415V~ 5G4.0sq mm cable 2.2m
Output	1 CEE L Socket 32A-IP67 2P+E 230V~ 1 CEE L Socket 32A-IP67 3P+N+E 415V~
Protection fuse	1 RCD 40A 4P 0.03A 400V~ 1 MCB 32A 1P 230V~
Protection degree	IP55 Waterproof



B06MD01-4



Dimension	340 × 136 × 94.5
Input:	1 CEE L plug 16A-IP44 2P+E 230V~ 3G2.5sq mm cable 2.2m
Output	4 SCHUKO socket 16A-IP44 2P+E 230V~
Protection	1 RCD 25A 2P 0.03A 230V~
fuse	4 MCB 16A 1P 230V~
Protection degree	IP44 Splashproof